Poly Flex Data Sheet

Product: Steel Half Coupling Series: Parallel Clamp

Model: 434F Parallel Clamp Half Coupling

Material Specification

· CNC Lathe - CS1020 Steel

· All Metal Parts - SA5 Cobalt Zinc Plated

Weight Of Coupling	
Kg	Ibs
2.3	5.07


Available Shaft Sizes	
Metric	Inches
16mm to 38mm	5/8" to 1 1/2"


Available Keyways	
Metric	Inches
5mm - 3mm Deep	3/16" - 7/64" Deep
6mm - 3.5mm Deep	1/4" - 7/64" Deep
8mm - 4mm Deep	5/16" - 11/64" Deep
10mm - 4mm Deep	3/8" - 3/16" Deep
12mm - 4mm Deep	7/16" - 3/16" Deep
14mm - 5mm Deep	1/2" - 3/16" Deep
16mm - 5mm Deep	9/16" - 13/64" Deep
18mm - 5.5mm Deep	5/8" - 13/64" Deep
	3/4" - 7/32" Deep

Available Grub Screws	
8mm	10mm

Transmission Cross Reference

Matching Component to 434 Shaft Couplings





Bolt Torque Settings		
lb-ft	N-m	
70	95	

The following data is supplied as a guide only. Specifications are subject to change without notice.

Date: 13/06/2023

Copyright © 2022 Poly Flex Group Pty Ltd.



26 - 28 Tubbs Street Clontarf, Qld. 4019. Australia

07 3284 2799 : Int Code +61 info@polyflex.com.au www.polyflex.com.au

